



— SPECIFICATIONS

Catalog No.	Pressure Rating(PSI)	Orifice Size	Port Type	BODY Material
CV110S08	5,500	ø5	H508	STS316CW

— Note
1. All dimensions for reference only and subject to change.

0	FOR APPROVAL	09/03		
REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY
DESIGN SECTION				

Website		Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com					
3	SLEEVE	5,500 1/2"	FA11SS08	STS 304	2	EA	-
2	GLAND	5,500 1/2"	FA11GS08	STS 304	2	EA	-
1	O-RING CHECK VALVE	5,500 1/2"	CV110S08	STS 316CW	1	EA	-
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
	PART CODE				FOR ONE SET		
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2-0.4 X 45°		UNIT: MM		PROJECT LOW PRESSURE CHECK VALVE			
General tolerance is given in KS B ISO 2768-1				TITLE 5,500PSI 1/2" O-RING TYPE			
NOMINAL DIM.(MM)		CLASS OF FINISH		APPD BY CHD BY DED BY DRW BY WORK NO.			
OVER	UNDER	TOL.	√ = √, 200S, ~	SCALE 1:1 DRW DATE DWG NO.			
0.5	6	±0.1	√ = √, 50S, ∇	REV. NO.			
6	30	±0.2	√ = √, 12.5S, ∇				
30	120	±0.3	√ = √, 3.2S, ∇				
120	315	±0.5	√ = √, 0.8S, ∇				
315	1000	±0.8					
1000	2000	±1.2					
OVER 2000		±1.5					