



— SPECIFICATIONS

Catalog No.	Pressure Rating(PSI)	Port type	Orifice Size(ϕ)	Material
NV20VS04-S	20,000	H2004	3.2	STS16CW

— Note

1. All dimensions for reference only and subject to change.

REV NO.	DESCRIPTION	DRAWING	REVIEWED BY	APPROVED BY
0	FOR APPROVAL	/		
DESIGN SECTION				

Website		Main site : http://www.hiflux.com Shopping mall : http://www.hifluxmall.com					
3	COLLAR	20,000PSI 1/4"	FA20RS04	STS304CW	2	EA	-
2	GLAND	20,000PSI 1/4"	FA20GS04	STS304CW	2	EA	-
1	NEEDLE VALVE	20,000PSI 1/4"	NV20VS04-S	-	1	EA	-
ITEM	NAME OF PART	SPEC	Catalog No.	MATERIAL	QUANTITY	UNIT	REMARK
	PART CODE	DESCRIPTION			FOR ONE SET		
MATERIAL LIST FOR ONE SET							
No indication chamfer 0.2-0.4 X 45°		UNIT: MM	PROJECT MEDIUM PRESSURE NEEDLE VALVE				
General tolerance is given in KS B ISO 2768-1			TITLE NEEDLE VALVE STRAIGHT				
NOMINAL DIM.(MM)		CLASS OF FINISH	20,000PSIG 1/4"				
OVER	UNDER	TOL.	APPD BY CHD BY DED BY DRW BY WORK NO.				
0.5	6	±0.1	SCALE 1:1				
6	30	±0.2	DRW DATE DWG NO.				
30	120	±0.3					
120	315	±0.5					
315	1000	±0.8					
1000	2000	±1.2					
OVER 2000		±1.5					